

TORQUE MOTOR

TMM0530-070

PERFORMANCE		Winding codes	3VBN	3VDN
		UNIT	FREE AIR CONVECTION (with glued stator)	FREE AIR CONVECTION (with glued stator)
Tp	Peak torque	Nm	2330	2330
Tc	Continuous torque	Nm	569	569
Ts	Stall torque	Nm	437	437
Kt	Torque constant	Nm/Arms	56.4	28.2
Ku	Back EMF constant (*)	Vrms/(rad/s)	32.6	16.3
Km	Motor constant	Nm/√W	21.8	21.8
R20	Electrical resistance at 20°C (*)	Ohm	4.48	1.12
L1	Electrical inductance (*)	mH	54.0	13.5
Ip	Peak current	Arms	79.6	159
Ic	Continuous current	Arms	10.3	20.6
Is	Stall current	Arms	7.81	15.6
Pc	Max. continuous power dissipation	W	1020	1020

SPECIFICATIONS		UNIT		
Udc	Nominal input voltage	VDC	600	600
τth	Thermal time constant	s	2490	2490
Rth	Thermal resistance	K/W	0.108	0.108
2p	Number of poles	-	88	88
J	Rotor inertia	kg.m ²	0.645	0.645
Mr	Rotor mass	kg	13.4	13.4
Ms	Stator mass	kg	33.0	33.0
Td	Max. detent torque (average to peak)	Nm	20	20
ns	Stall speed	rpm	0.0055	0.0055

Notes: (*) terminal to terminal. Ambient temperature = 20 °C. Max. coil temperature = 130 °C.
 Hypothesis and tolerances are in ETEL's Handbook. Stator connected to a total surface of 0.35 m² and rotor to a total surface of 0.240 m²

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

